

Technical specifications

Valtra Inc.
 FI-44200 Suolahki, Finland
 Tel. +358 20 455 01
 Fax +358 20 455 0533
 www.valtra.com

Model	A75L	A85L	A95L
Engine, SisuDiesel	4 stroke diesel, direct injection, turbo		
Cylinders	3 vertical in-line, single cylinder head, interchangeable wet liners		
Displacement	3 300 cc		
Intercooler	Intercooler	Intercooler	Intercooler
Max. power kW (hp) / r/min, ISO 14396	54 (74) / 2150	65 (88) / 2150	72 (98) / 2150
Max. torque Nm/r/min, ISO 14396	296/1400	324/1400	359/1100
Injection system	Rotary injection pump with built-in regulator		
Power train	Dual 295 mm dry disc, mechanically operated (pedal)		
Clutch	Synchronized with 12 forward and 12 reverse gears. Mechanical differential lock with electro-hydraulic operation		
Gearbox	540/1000 r/min or 540/540E (750) r/min. Hand operated lever		
PTO	44.5	49.5	54
Max. power at 540 r/min	46.5	51.5	58
Max. power at 1000 r/min	Three point linkage category II with draft, position control and lowering speed adjustment		
Hydraulic system	28	33	33
Max. lifting capacity, kN	15 kW (17MPa, 53L/M)		
Max. pressure, MPa	Gear pump		
Max. power	55 l/min		
Pump type	Washable metal strainer		
Max. pump capacity	Hydrostatic		
Suction filter	4WD 4,8 / 5,2 2WD 3,6		
Steering	Oil bath multidisc with independent action		
Turning radius, m (without brakes / with brakes)	In 4WD models		
Brakes	Mechanically operated, acting on running brakes		
Four-wheel brakes	Dimensions for standard tractor		
Parking brake	3957 - 4096		
Specifications 2WD / 4WD	2506 - 2645		
Length (with ballast weights), mm	2137 - 2175		
Max. height (to exhaust pipe), mm	2244 - 2387		
Max. width, mm	Front: 442 - 495 Rear: 455 - 485		
Wheel base, mm	70 (95 with auxiliary)		
Ground clearance (under axle), mm	Powered front axle (4WD). Automatic diff. lock. Beam design (2WD)		
Fuel tank capacity, l	3000 - 3120		
Front axle			
Weight, kg			

Speeds km/h (tyres 18.4-34 or 14.9-38)

Tyres	LL	M	H
2WD	10.00-16/16,9-30	11.00-16/18,4-34	
4WD	13.6-24/13,6-38	14.9-24/18,4-34	
Other sizes also available			

Speeds km/h (tyres 18.4-34 or 14.9-38)

Tyres	LL	M	H
1	0.85	3.51	12.06
2	1.33	5.13	17.86
3	1.90	7.51	26.03
4	2.66	10.73	36.96

Specifications may change, all rights reserved.
 Tractors shown here may be equipped with optional or other equipment.



Accessories

- Fixed ROPS frame
- Fixed ROPS frame with sunroof
- Foldable ROPS frame
- Field lights on upper ROPS frame
- Front weights - (six or eight, 40kg)
- Rear wheel weights - (four, 34-38", 80kg)
- Rear wheel weights - (four, 30", 70kg)
- Fuel strainer
- Front mudguards
- Extra fuel tank 24L
- 7 pin socket. Licence plate.
- Control stop
- Spool valves
- Wagon hitch
- Pick-up hitch
- Industrial and forest tyres
- Eight colour choices